



Revision Number: 004.0

Issue date: 08/07/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	TEROSON MS 5510 WH known as LOCTITE® 5510™ ELASTIC ADHESI	IDH number:	1562042
Product type:	adhesive and sealant	Item number:	1562042
Restriction of Use:	None identified	Region:	United States
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Contact information:	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkeln.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.
CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention:	Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	40 - 50
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	68515-49-1	20 - 30

Titanium dioxide	13463-67-7	1 - 5
Trimethoxyvinylsilane	2768-02-7	1 - 5
Octadecanoic acid	57-11-4	1 - 5
Quartz (SiO ₂)	14808-60-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Wipe off with paper towel or cloth. Wash with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Flush eye(s) immediately with plenty of water. If eye irritation persists, consult a specialist.
Ingestion:	Do not induce vomiting. If symptoms develop and persist, get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet.
Special firefighting procedures:	Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Oxides of silicon. Oxides of nitrogen. Acrid smoke and fumes. Irritating vapors. Toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not let product enter drains.
Clean-up methods:	Rinse spill area with water. Spilled material will solidify. Sweep up spilled material and place in a closed container for disposal. Avoid creating dust.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.
Storage:	Store in a cool, dry, well-ventilated area. Store in original container until ready to use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m ³ TWA Total dust.	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	None	None	None	None
Titanium dioxide	10 mg/m ³ TWA	15 mg/m ³ PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
Trimethoxyvinylsilane	None	None	None	None
Octadecanoic acid	10 mg/m ³ TWA Inhalable fraction. 3 mg/m ³ TWA Respirable fraction.	None	None	None
Quartz (SiO ₂)	0.025 mg/m ³ TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.05 mg/m ³ TWA (Respirable dust.) 0.025 mg/m ³ OSHA_ACT (Respirable dust.) 0.05 mg/m ³ PEL Respirable dust.	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid, Paste
Color:	White
Odor:	Slight
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	> 93 °C (> 199.4 °F)
Melting point/ range:	Not available.
Specific gravity:	1.4
Vapor density:	Not available.

Flash point:	> 93 °C (> 199.4 °F) ; Estimated
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	1.74 %; 24.5 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of silicon. Oxides of nitrogen. Acrid smoke and fumes. Toxic fumes. Irritating vapors. Methanol is liberated slowly upon exposure to moisture.
Incompatible materials:	Acids. Oxidizing agents. Isocyanates.
Reactivity:	Not available.
Conditions to avoid:	Excessive heat. Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors from uncured sealant may cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	None	Irritant
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Trimethoxyvinylsilane	None	Irritant, Allergen
Octadecanoic acid	Oral LD50 (Rat) = 4.6 g/kg	Irritant
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	No	No	No
Titanium dioxide	No	Group 2B	No
Trimethoxyvinylsilane	No	No	No
Octadecanoic acid	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Polyamide resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Polyamide resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III
Marine pollutant: Polyamide resin

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health
CERCLA/SARA Section 313: None above reporting de minimis.
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Cara R. Rivera, Regulatory Affairs Specialist

Issue date: 08/07/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.